

# Freight containers — Mechanical seals

ICS 55.180.10

## National foreword

This Draft for Development reproduces verbatim ISO/PAS 17712:2003.

### This publication is not to be regarded as a British Standard.

It is being issued in the Draft for Development series of publications and is of a provisional nature because the testing procedures it refers to, although currently used in practice, have yet to be proven as generally applicable, repeatable and verifiable. It should be applied on this provisional basis, so that information and experience of its practical application may be obtained.

A PAS is a Technical Specification not fulfilling the requirements for a standard, but made available to the public and established in an organization operating under a given procedure.

Comments arising from the use of this Draft for Development are requested so that UK experience can be reported to the international organization responsible for the Technical Specification. A review of this publication will be initiated not later than 3 years after its publication by the international organization so that a decision can be taken on its status at the end of its 3-year life. Notification of the start of the review period will be made in an announcement in the appropriate issue of *Update Standards*.

According to the replies received by the end of the review period, the responsible BSI Committee will decide whether to support the conversion into an international standard, to extend the life of the Technical Specification for another 3 years or to withdraw it. Comments should be sent in writing to the Secretary of BSI Technical Committee TW/1, Freight containers and swap bodies, at British Standards House, 389 Chiswick High Road, London W4 4AL, giving the document reference and clause number and proposing, where possible, an appropriate revision of the text.

A list of organizations represented on this committee can be obtained on request to its secretary.

### Cross-references

The British Standards which implement international publications referred to in this document may be found in the BSI Catalogue under the section entitled "International Standards Correspondence Index", or by using the "Search" facility of the *BSI Electronic Catalogue* or of British Standards Online.

### Summary of pages

This document comprises a front cover, an inside front cover, the ISO/PAS title page, pages ii and iii, a blank page, pages 1 to 6, an inside back cover and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

### Amendments issued since publication

Amd. No.	Date	Comments

This Draft for Development was published under the authority of the Standards Policy and Strategy Committee on 18 December 2003

© BSI 18 December 2003

ISBN 0 580 43107 X

PUBLICLY  
AVAILABLE  
SPECIFICATION

**ISO/PAS**  
**17712**

First edition  
2003-10-01

---

---

**Freight containers — Mechanical seals**

*Réipients de fret — Joints mécaniques*



Reference number  
ISO/PAS 17712:2003(E)



## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of normative document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote;
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

An ISO/PAS or ISO/TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/PAS or ISO/TS is confirmed, it is reviewed again after a further three years, at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/PAS 17712 was prepared by Technical Committee ISO/TC 104, *Freight containers*. It is issued initially as a Publicly Available Specification (PAS) due to the immediate need for clarification and guidance with regard to security seals used in conjunction with freight container transportation. It has been prepared based on existing material available from national customs organizations, national testing bodies and the World Customs Organization.



# Freight containers — Mechanical seals

## 1 Scope

This Publicly Available Specification (PAS) establishes uniform procedures for the classification, acceptance, and withdrawal of acceptance of mechanical freight container seals. It provides a single source of information on mechanical seals which are acceptable for securing freight containers in international commerce.

This Publicly Available Specification is not applicable to special-purpose seals, such as fibre-optic and sophisticated electronic seals.

## 2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 2.1

#### **security seal**

passive, one-time locking device that is used to provide a reliable indicator of tampering (unauthorized removal or attempted removal) or entry

NOTE In addition, by virtue of its construction, the security seal provides limited resistance to an intentional or unintentional attempt to open it and enter the freight container that is sealed with the seal. Security seals require inspection to indicate whether tampering has occurred or entry has been attempted.

### 2.2

#### **high security seal**

security seal that is constructed and manufactured of material such as metal or metal cable with the intent to delay intrusion

NOTE High security seals generally must be removed with quality bolt cutters or cable cutters. They require inspection to indicate whether tampering has occurred or entry has been attempted.

### 2.3

#### **indicative seal**

seal that is constructed and manufactured of material that can easily be broken by hand or by using a simple snipping tool or shear

NOTE Indicative seals require inspection to indicate whether tampering has occurred or entry has been attempted.

## 3 Mechanical seal types and requirements

### 3.1 Types of mechanical seal

#### 3.1.1 Wire seals

Wire seals consist of a length of wire secured in a loop by some type of seizing device.

EXAMPLES Crimp wire, fold wire and cup wire seals.

### 3.1.2 Padlock seals

Padlock seals consist of a locking body with a bail attached.

EXAMPLES Wire shackle padlock (metal or plastic body), plastic padlock and keyless padlock seals.

### 3.1.3 Strap seals

Strap seals consist of a metal or plastic strap secured in a loop by inserting one end into or through a protected (covered) locking mechanism on the other end.

### 3.1.4 Cable seals

Cable seals consist of a cable and a locking mechanism. On a one-piece seal, the locking or seizing mechanism is permanently attached to one end of the cable. A two-piece cable seal has a separate locking mechanism which slips onto the cable or prefabricated cable end.

### 3.1.5 Bolt seals

Bolt seals consist of a metal rod, threaded or unthreaded, flexible or rigid, with a formed head, secured with a separate locking mechanism.

### 3.1.6 Cinch or pull-up seals

Cinch or pull-up seals are indicative seals consisting of a thin strip of material, serrated or non-serrated, with a locking mechanism attached to one end. The free end is pulled through a hole in the locking mechanism and drawn up to the necessary tightness. Cinch or pull-up type seals may have multiple lock positions. These seals are generally made of synthetic materials such as nylon or plastic. They should not be compared to simple electrical ties.

### 3.1.7 Twist seals

Twist seals are made of steel rod or heavy-gauge wire of various diameters, which is inserted through the locking fixture and twisted around itself by use of a tool.

### 3.1.8 Scored seals

Scored seals consist of a metal strip which is scored perpendicular to the length of the strip. The strip is passed through the locking fixture and bent at the score mark. Removal of the seal requires bending at the score mark which results in breakage of the seal.

### 3.1.9 Label seals

Label seals are frangible seals consisting of a paper or plastic backing with adhesive. The combination of backing and adhesive are chosen to cause the seal to tear when removal is attempted.

### 3.1.10 Barrier seals

Barrier seals are designed to provide a significant barrier to container entry. A barrier seal may, for example, enclose a portion of the inner locking rods on a container. Barrier seals may be designed to be reusable.

## 3.2 General requirements

**3.2.1** Security and high security seals shall be strong and durable so as to prevent accidental breakage, early deterioration (due to weather conditions, chemical action, etc.) or undetectable tampering under normal usage.

**3.2.2** Seals shall be capable of being affixed easily and quickly.

**3.2.3** Seals shall be identified by unique marks (such as a logotype) and numbers that are readily legible; markings intended for unique identification of the seal shall be considered permanent. Any modification of markings shall require irreversible physical, chemical, heat or other destruction of the security seal.

**3.2.4** Seals shall be designed and constructed so as not to permit removal or undoing without breaking, or tampering without leaving readily apparent traces.

**3.2.5** Seals, with the exception of barrier seals, shall be designed so as not to permit use more than once.

**3.2.6** Seals shall be made as difficult as possible to copy or counterfeit.

### **3.3 Identification marks**

**3.3.1** Seals intended for use on freight containers moving under customs laws as instruments of international trade shall be separately approved and marked as determined by the relevant customs organization or competent authority.

**3.3.2** If the seal is to be purchased and used by customs, the seal or fastening, as appropriate, shall be marked to show that it is a customs seal by application of unique words or markings designated by the appropriate customs organization and a unique identification number.

**3.3.3** If the seal is to be used by private industry (i.e. a shipper, manufacturer or carrier), it shall be clearly and legibly marked with a unique identification number. It may also be marked with a company name or logo.

### **3.4 Evidence of tampering**

**3.4.1** Different seal types evidence tampering in different ways, but one common test for tampering, regardless of seal type, is easy opening of the seal under hand pressure.

**3.4.2** Cable and wire seals can also evidence tampering by a frayed appearance at the point where the wire or cable meets the locking portion of the seal.

**3.4.3** Bolt, rod and padlock-type seals can evidence tampering by scratches or nicks on the body of the seal, indicating attempted prying or picking of the lock mechanism. Threaded bolts can be bent after installation to upset the threads and prevent undetected removal of the locking mechanism. The use of a plastic coating on these types of seals can promote the detection of tampering.

**3.4.4** Other types of seal can evidence tampering by scratches or nicks adjacent to the locking mechanism or deformation of the locking mechanism.

### **3.5 Customs acceptance**

**3.5.1** Seals shall be manufactured under a controlled process, as evidenced by a suitable, externally audited manufacturing and testing processes quality control process, for example by ISO 9000 series certification.

**3.5.2** Seals will be considered as acceptable for use and/or purchase as soon as the manufacturer attests that the seals have been tested and meet or exceed the standards provided in Clause 4 and that they also meet the other requirements of this Publicly Available Specification. They will continue to be considered acceptable until such time as it is demonstrated that they do not meet the standards or they are withdrawn from the marketplace by the manufacturer. A manufacturer should notify the appropriate customs authority whenever a seal is so withdrawn.

**3.5.3** A manufacturer may attest to the qualification of a specific seal, or to an entire product line of seals as of a certain date. Any addition of a seal to a group of seals attested to as a group would require specific acceptance of that seal by customs.

**3.5.4** All testing of seals deemed necessary before customs acceptance will be done by the manufacturer or by a private laboratory, and not by customs. However, customs reserves the right to test, or to have tested, seals that have been accepted by customs.

**3.5.5** Only seals classed as high security or security seals based on the test protocols set forth in Clause 4 shall be acceptable for use as customs seals.

### 3.6 Test fixture configuration

The general type of seal and its configuration shall be used to configure the appropriate test fixture. Seals shall be classified as high security, security or indicative based on their certified performance under the tests described in Clause 4.

## 4 Testing

### 4.1 Tensile test

A pull test shall be conducted to determine the strength of a seal's locking mechanism. The test fixture shall apply a uniform load to the seal in a manner that simulates reversal of the motion used to lock the seal. The load shall be slowly applied until the seal forcibly opens or is otherwise broken.

The seal shall be classified based on the tensile force recorded at the time of failure of the seal based on the criteria set forth in Table 1.

**Table 1 — Tensile test seal classification requirements**

Load to failure kN <sup>a</sup>	Seal classification
10,0 <sup>b</sup>	High security seal
2,27	Security seal
< 2,27	Indicative seal
<p><sup>a</sup> 1 J = 0,737 562 1 ft-lbf 1 N = 0,224 808 9 lbf 1 kg-f = 2,204 585 5 lbf 1 N·m = 0,737 562 1 ft-lbf</p> <p><sup>b</sup> A value of 7,5 kN is acceptable for those seals specifically designed to fail at a location that is plainly visible and precludes reassembly of the seal such that the failure would not be apparent.</p>	

### 4.2 Shear test

**4.2.1** A shear test shall be conducted to test the ability of a seal to withstand cutting with shearing blades, as might be implemented with bolt cutters. The cutting blades used in the test fixture shall be sufficiently well aligned that seals are cut and not merely deformed as might occur with a thin, flexible seal and misaligned blades. The compressive load shall be applied slowly until the seal is severed.

**4.2.2** The seal shall be classified based on the compressive load recorded at the time of failure of the seal based on the loads set forth in Table 2.

**Table 2 — Shear test seal classification requirements**

Load to failure kg-f <sup>a</sup>	Seal classification
341	High security seal
227	Security seal
< 227	Indicative seal
<sup>a</sup> 1 J = 0,737 562 1 ft-lbf 1 N = 0,224 808 9 lbf 1 kg-f = 2,204 585 5 lbf 1 N·m = 0,737 562 1 ft-lbf	

### 4.3 Bending test

**4.3.1** The bending test is run to determine the resistance of a seal to failure under bending loads. How the test is run shall be based on the subclassification of the seal as either flexible or rigid. Flexible seals shall be tested for their ability to resist repeated bending loads without failure. Rigid seals shall be tested to determine their resistance to deformation by bending.

**4.3.2** For flexible seals, fix the locking end and flex the material adjacent to this fixed end repeatedly through an arc of 180° until failure. Record the number of cycles through this 180° arch and base classification of the seal on the number of cycles shown in Table 3.

**4.3.3** For single-shaft rigid seals, fix the locking end and then fit a tube or other suitable lever over the remaining portion of the seal. Apply a load on the lever so as to bend the seal 90°. Record the load required to bend the seal and the distance above the fixed end of the seal (the moment arm) that the load is applied. Base classification of the seal on the maximum bending moment recorded and that shown in Table 3.

**4.3.4** For rigid seals with two shafts such as in a padlock, fix the locking end and then fit a bar or rod through the opening between the two shafts. Rotate the rod or bar until it is in contact with both shafts. Continue to rotate the bar in the same direction an additional 90°. Record the torsional force needed to achieve the 90° rotation or to cause failure of the locking mechanism if that occurs prior to achieving the 90° rotation. Base classification of the seal on the maximum bending moment recorded and that shown in Table 3.

**Table 3 — Bending test seal classification requirements**

Cycles to failure (flexible seals)	Bending moment to failure (rigid seals) N·m <sup>a</sup>	Seal classification
501	50	High security seal
251	22	Security seal
< 251	< 22	Indicative seal
<sup>a</sup> 1 N·m = 0,737 562 1 ft-lbf		

### 4.4 Impact test

**4.4.1** The impact test shall be run to determine the resistance of the seal to an impact load at 18 °C and – 27 °C. The test fixture shall be devised so the impact load is applied at the locking mechanism of the seal in the direction opposite the direction used in locking the seal. The impact load shall be applied five times at a load equivalent to 13,56 J. Subsequent impact test sequences shall be run at a load that is 13,56 J higher than the previous five impact loads. Impacts shall be run until the seal fails or successfully withstands five impacts at 40,68 J. A second seal shall be tested at the second temperature.

**4.4.2** If the seal fails prior to completion of the five impact cycles, it shall be classed based on the next lower set of values. The value at which the seal fails shall be recorded and used to determine the seal's classification. The values set forth in Table 4 shall be the basis for this determination.

Table 4 — Impact test seal classification requirements

Low temperature impact load J <sup>a</sup>	High temperature impact load J <sup>a</sup>	Seal classification
40,68	40,68	High security seal
27,12	27,12	Security seal
< 27,12	< 27,12	Indicative seal
<sup>a</sup> 1 J = 0,737 562 1 ft-lbf 1 N = 0,224 808 9 lbf 1 kg-f = 2,204 585 5 lbf 1 N·m = 0,737 562 1 ft-lbf		



---

---

# BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

## Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover.  
Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

## Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001.  
Fax: +44 (0)20 8996 7001. Email: [orders@bsi-global.com](mailto:orders@bsi-global.com). Standards are also available from the BSI website at <http://www.bsi-global.com>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

## Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre.  
Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: [info@bsi-global.com](mailto:info@bsi-global.com).

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.  
Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001.  
Email: [membership@bsi-global.com](mailto:membership@bsi-global.com).

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsi-global.com/bsonline>.

Further information about BSI is available on the BSI website at <http://www.bsi-global.com>.

## Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager.  
Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553.  
Email: [copyright@bsi-global.com](mailto:copyright@bsi-global.com).